

# FANTECH VENTILATION FANS



**TIP:** Use these remote mounted fans for exhausting bathrooms, laundry rooms, basements and crawl spaces. Remote mounted fans can exhaust from multiple points in large rooms or from separate rooms with one fan. They can be used for dryer boosting, kitchen range hoods or for re-circulating heat or AC within a building. See page 12 for more ideas.



## FR SERIES IN-LINE FANS

- Can be installed vertically or horizontally
- Thermoplastic housing
- UL Listed for outdoor use and wet locations

	MODEL	CFM	POWER	DUCT
<b>5501.10</b>	FR 100	100	19w	4"
<b>5501.101</b>	FR 110	150	80w	4"
<b>5501.11</b>	FR 125	120	18w	5"
<b>5501.110</b>	FR 140	190	61w	6"
<b>5501.12</b>	FR 150	230	71w	6"
<b>5501.13</b>	FR 160	260	129w	6"
<b>5501.15</b>	FR 200	360	122w	8"
<b>5501.16</b>	FR 225	400	137w	8"
<b>5501.17</b>	FR 250	600	241w	10"



## FG SERIES IN-LINE FANS

- Can be installed vertically or horizontally
- Airtight, galvanized steel housing
- Use with range hoods and commercial applications

	MODEL	CFM	POWER	DUCT
<b>5501.301</b>	FG 4	110	20w	4"
<b>5501.302</b>	FG 4XL	150	71w	4"
<b>5501.303</b>	FG 5	130	20w	5"
<b>5501.304</b>	FG 5XL	190	73w	5"
<b>5501.305</b>	FG 6	270	72w	6"
<b>5501.306</b>	FG 6XL	450	153w	6"
<b>5501.307</b>	FG 8	410	119w	8"
<b>5501.308</b>	FG 8XL	470	142w	8"
<b>5501.309</b>	FG 10	480	138w	10"
<b>5501.312</b>	FG 12	680	181w	12"



## DRYER BOOST KIT

- Use with dryers that have duct runs between 30' – 130' equivalent length
- Mount at least 15' from the dryer
- Senses pressure and runs in 10 minute cycles when the drier is on
- DBF-4XL — Galvanized housing, pressure switch attached, 3 prong plug attached, insert pressure tube in the duct
- DBF-110 — Thermoplastic housing, pressure switch attached with tube installed in the fan collar, bring power to the fan junction box — no plug
- 4" duct, 150 CFM, 83w

**5501.391** Fantech Dryer Boost DBF-4XL with Pressure Switch

**5501.39** Fantech Dryer Boost DBF-110 with Pressure Switch

**5501.71** DB-10 Pressure Switch Only