

WHOLE HOUSE EXHAUST FANS




TAMARACK TECHNOLOGIES WHOLE HOUSE FANS

These Whole House Fans offer an energy efficient way to cool down your house without using air conditioning when the outside temperature is lower than the inside temperature.

High quality, balanced fan motors draw outside air into your home through doors and windows while blowing indoor air up into the attic where it leaves the house through ridge, soffit or gable vents. Approximately one square foot of net free area is required for every 1,000 CFM of air movement.

Unlike other whole house fans, these units include a motorized, insulated cover that closes when not in use, keeping the attic air isolated from the main house.

Installation is easy. These fans are designed to fit either 16" or 24" on-center framing. Simply box in the unit, make the electrical connections and install the ceiling grille. Units with remote controls simply plug in to a 3-prong socket.



HV-1000

- 1,000 CFM
- 1 speed
- Service up to 1,200 square feet

5502.15 HV-1000 R-22 with hardwire wall switch

5502.161 HV-1000 R-38 with hardwire wall switch

5502.152 HV-1000 whole house remote control upgrade

HV-1600 with Remote Control

- 1,600 CFM
- 2 speed
- Service up to 2,000 square feet

5502.166 HV-1600 R-22 with 2 speed remote

5502.163 HV-1600 R-38 with 2 speed remote

PRODUCT COMPARISON

	HV-1000	HV-1600
Airflow — CFM	1,000	1,600
Control	HW wall switch	2-speed remote
Suitable House Size	Up to 1,200 SF	Up to 2,000 SF
Power Usage	112w	276w
R-Value of Door	R-22 or R-38	R-22 or R-38
Rough Opening	14.5" x 22.5"	14.5" x 22.5"
Grille Dimension	16" x 26"	16" x 26"
Net Free Area required in the attic for air to move out	1 square feet	1.5 square feet
Clearance requirement	12" min	12" min

MANUFACTURED HOUSING BATH FAN REPLACEMENT — 7"

The Mainstream Fan is a direct replacement for ceiling mounted, through the roof exhaust fans found in a majority of manufactured housing units. This fan gives the installer the opportunity to replace a noisy, in-efficient fan with a quiet energy efficient unit. The fan installs from the inside, comes with a new grille and utilizes the existing roof cap.

- Easy to install — replaces existing 7" fan
- Quiet — 1.5 sones
- 90 CFM
- Rated for continuous operation
- Energy efficient — draws 19 watts
- Durable back draft damper keeps cold air from coming in when not in use
- Includes ceiling grille
- Optional switch available for timed ventilation
- 5 year product warranty

5502.09 Mainstream Fan with Timer

5502.10 Mainstream Fan Only



National distributor shipping direct throughout the United States
TO PLACE ORDERS OR FOR MORE INFORMATION:
800/876/0660 ♪ **FAX 888/440/4219**
WISCONSIN 800/962/7015 ♪ **WISCONSIN FAX 920/757/6452**
 HEADQUARTERS 40 Washington Street, Westborough, Massachusetts 01581 • www.efi.org/wholesale