

TIMERS AND CONTROLS



30-15-10-5 OR 60-30-20-10 ELECTRONIC TIMER



- 4 wires
- Fits in a single gang box, can be installed in 2 or 3 gang boxes
- Decora style faceplate

Allows the homeowner to choose the appropriate amount of run time. There are five small buttons with LED lights that indicates run time. "Off" can be used to cancel the run.

- 5010.71** 30-15-10-5 Minute Timer — White
- 5010.70** 30-15-10-5 Minute Timer — Ivory
- 5010.743** 60-30-20-10 Minute Timer — White
- 5010.744** 60-30-20-10 Minute Timer — Ivory

120-60-30-15 MINUTE TIMER

- 3 wires plus ground
- Fits in a single gang box, can be installed in 2 or 3 gang boxes
- Decora style faceplate

Allows the homeowner to choose the appropriate amount of run time. One switch comes with white and ivory over lays. Finger pad style power button used to both start the run or cancel it.



- 5010.046** 120-60-30-15 Minute Timer — White/Ivory

60 MINUTE MECHANICAL TIMER

- Requires 2 wires
- Fits into a single gang box, can be installed in 2 or 3 gang boxes
- Comes with white and ivory plates for both Toggle and Decora style

A mechanical spring wound timer that allows the homeowner to turn the fan on for a period of up to 60 minutes.



- 5010.045** 60 Minute Timer — White/Ivory

FAN CONTROLS — TIMED LOW SPEED VENTILATION WITH BOOST



- 3 Wires, 120v, 2.5 amp
- Fits in single or multiple gang boxes
- Use up to 3 auxiliary units with one main unit
- Allows low speed ventilation with 20 minute boost

Ideal control to install when using a remote mounted fan for venting multiple points. Use the Main Control — VT20M — to set the number of minutes per hour and the speed at which the fan will run. The same number of minutes per hour will repeat throughout the day. Can be set to run the fan continuously at low speed.

Use up to 3 auxiliary controls in other locations. Once installed, pushing the pad on either the main control or one of the auxiliary controls will boost the fan to high speed for 20 minutes. Blue LED indicates boost mode. Helps builders meet the ventilation requirement of ASHRAE 62.2.

- 5510.36** Ventech Main Control — VT20M
- 5510.37** Ventech Auxiliary Control — VT20A

24 HOUR ELECTRONIC PROGRAMMABLE TIMER

- 3 Wires
- Fits a single gang box
- Allows the homeowner to use an exhaust fan for background ventilation
- Two operating modes — manual and auto

The installer may set up to 7 on/off cycles within a 24 hour period. Once the cycles are set, each individual cycle can be set for one day or all seven days. Even while running in the auto mode, the plate can be used to turn the switch on and off as needed. The LED screen displays the date and time.



- 5010.81** Seven Day Electronic Timer — White

National distributor shipping direct throughout the United States
TO PLACE ORDERS OR FOR MORE INFORMATION:
800/876/0660 ♪ **FAX 888/440/4219**
WISCONSIN 800/962/7015 ♪ **WISCONSIN FAX 920/757/6452**
 HEADQUARTERS 40 Washington Street, Westborough, Massachusetts 01581 • www.efi.org/wholesale